

CONTROLS & FEATURES

WARNING &

POWER / ON LEDs

Green LED flases continuously when the unit is activated, during normal scanning operation.

Red LED is activated when a storm has approached within the User-determined warning range.

ENTER

Used to select Menu items, enter values, and exit Menu and return to normal operations.

POWER ON/OFF

SPEAKER

Speaker for the Audible Alarm



INTELICHARGE AC ADAPTER JACK

BATTERY COMPARTMENT DOOR

LCD TEXT SCREEN

Used to select Menu items, enter values, and exit Menu

SCROLL UP / DOWN BUTTONS

Used to access and move through the unit's menu.

TONE ON/OFF

Turns audible alarm on and off

- **Storm Detection Range: 0-130 miles / 210kM**
- **Displays Storm Distance from 0-75 miles / 120kM**
- **Intelicharge Rechargeable Battery System**
- **Rechargeable worldwide with included Intelicharge Power Adapter on any current & plug configuration**
- **Communicates in Miles and Kilometers**
- **Visual and Audible Tone storm warnings settings**

- **Highest-grade durable plastic**
- **Fully gasketed (Water resistant)**
- **Easy-to-read backlit LCD text screen**
- **Text message library containing over 50 different storm messages including**
 - **Estimated Time to Arrival,**
 - **Approach Speed, Storm is Local,**
 - **Time to Clear,**
 - **Closest Activity,**
 - **Squall Line, Severe Storm, Multiple Storm Cells warnings, and more**